

# vLoc3-Cam SONDE LOCATOR

- 360° Guidance arrows
- Sonde locate and pushrod trace modes
- High visibility color 4.3"/10cm Display
- Locate utilities with optional transmitter
- **Optional Bluetooth connectivity**


The easiest, quickest and most accurate way to locate the position of a sonde is found in the vLoc3-Cam Sonde Locator. The bright full-color intuitive graphical display guides the user to the sonde using directional arrows. When directly on top of the sonde a large sonde icon appears confirming the sonde location and it's depth reading is confirmed.

The vLoc3-Cam includes multiple sonde frequencies making it compatible with the major push cameras and crawler cameras on the market. The Pushrod Trace mode shows a second display geared for tracing the path of the pushrod deployed in the pipe or tracing pipes with an optional portable transmitter.


The vLoc3-Cam comes with two Passive locate modes of Power and Radio which will detect the presence of live power lines, CATV, telephone and some metallic pipes which radiate 50Hz from nearby or overhead power lines. For active locating, with the use of a portable transmitter, the vLoc3-Cam comes with a choice of 33kHz or 83kHz frequency for tracing the pushrod. These frequencies are also ideal for water and gas utilities which generally are larger pipes with bell housings and gaskets, as well as locating small diameter drop wires and inducing signals through the soil, onto services when direct connecting is not an option.



Locate points - Shows null in front or behind the sonde with arrow directing to the sonde location



Sonde location - When directly over the sonde the sonde icon appears and depth is shown in upper left



Pushrod trace mode - Shows a peak response when locating. Compass indicator turns blue when in line with the pushrod.

### **Alkaline and Li-ion Batteries**

- Alkaline = typically 12-hours intermattiant use
- Li-ion = typically 27-hours intermittant use

## **USB Data Port**

- Update the receivers firmware

## **Accessory Port**

- Vehicle charging lead
- Charge li-ion battery

## **Antenna Configuration**

- Two sets of 3D antennas
- Omnidirectional antenna array



	vLoc3-Cam Receiver Specifications
Construction	High impact ABS injection molded housing
Weight & Dimensions	2.1kg / 321mm (L) x 124mm (W) x 676mm (H)
Display	Transmissive 480 x 272 Pixel, 16-bit Color, 10cm High Visibility LCD
Battery options	Six x AA Alkaline batteries Optional custom Lithium-ion rechargeable battery
Battery life	Lithium-ion - typically 27-hours intermittent use at 70°F (21°C)  Alkaline - typically 12 hours intermittent use at 70°F (21°C)
Operating frequencies	Sonde mode - 512Hz, 640Hz, 8,192kHz, 33kHz, and 83kHz Pushrod trace/line trace - choice of 33kHz or 83kHz Power - 50Hz Radio - 10kHz - 22.7kHz bandwidth
Operating modes	Sonde mode Pushrod/line trace mode
Environmental	IP65 and NEMA 4

# What's in the box












# **Popular Accessories**







Li-ion Rechargeable Battery





# **Compatible Transmitters**

## 1- Watt Transmitters







Loc-1Tx



Loc3-5Tx



Loc3-10Tx

Technoparc - 1 allée du Moulin Berger,

Vivax-Metrotech SAS

Tel: +33 (0)472 53 03 03

Fax: +33 (0)472 53 03 13

Email: salesfrance@vxmt.com

**Metrotech Vertriebs GmbH** 

69130 Ecully, France

# Vivax-Metrotech Corp. (Headquarters)

3251 Olcott Street, Santa Clara, CA 95054, USA T/Free: 800-446-3392

Tel: +1-408-734-1400 Fax: +1-408-734-1415 Email: sales@vxmt.com

### Vivax-Metrotech Ltd.

Unit 1, B/C Polden Business Centre, Bristol Road, Bridgwater, Somerset, TA6 4AW, UK Tel: +44(0)1793 822679 Email: salesUK@vxmt.com

## Ventas para América Latina

3251 Olcott Street, Santa Clara, CA 95054, USA T/Free: 800-624-6210 Tel: +1-408-734-1400

Fax: +1-408-743-5597

Email: VentasparaAmericaLatina@vxmt.com

### Vivax Canada Inc.

41 Courtland Ave Unit 6, Vaughan, ON L4K 3T3, Canada Tel: +1-289-846-3010 Fax: +1-905-752-0214 Email: CanadianSales@vxmt.com







D-96110 Schesslitz Tel: +49 954 277 227 43 Email: serviceGermany@vxmt.com



